

16 Gauge by RediFrame®

Shown with
standard
wood casing

RediFrame® steel frames have been chosen to outfit hospitality, multifamily, condominiums, office buildings, and assisted living facilities. The diversity is in our design. RediFrame is engineered to adapt to a variety of commercial and residential applications. Designed for Cased Opening, Single, Pair, Communicating, Dutch, and Double Egress... try RediFrame® first for special openings. RediFrame® is prefinished and can be specified to fit the hardware for any job. And, because we come prefinished, it installs over finished walls, creating a perfect jobsite finish.

Installation

The success of RediFrame® lies in the ease of installation, saving time and money. **RediFrame® is pre-finished, so installation occurs AFTER the wall is finished.**

Innovation

Dunbarton's continuing innovation has produced an adjustable strike, a patented casing corner bracket, and the Universal Hinge Prep, S56 safety guard emboss, heavy hinge prep, and an ABH 1000 / GJ100 series concealed overhead holder and stop. **We offer over 26 different electric strike preps, and 10 different concealed closure options.**

Security*

RediFrame® is designed to sleeve the wall, becoming an integral part of the wall system. In comparative impact testing 18 ga. RediFrame® withstood 850 impacts, over 500 more than hollow metal. The difference is the anchoring system. Not only does **RediFrame® sleeves the wall, but it anchors to the wall using at least 30 fasteners.**

Durability*

RediFrame® carries a Certification of Level A 1,000,000 cycles (ANSI 250.5-1994).

Testing

RediFrame® pledges to stay ahead of the field when it comes to fire ratings. We have taken the initiative to pass the most stringent and difficult tests to acquire the **Warnock Hersey standard in both neutral (UL 10B) and positive (UL 10C) pressure fire ratings.**

**Test results available upon request.*

RediFrame® 16 Gauge Standard Options:

- A-40 galvanized only
- 1-3/4" & 1-3/8" doors
- 17 standard wall sizes
- Custom profiles: 2-5/8" to 15"
- 5/8" stop height
- Demountable without damage to the finished wall, door or frame
- Standard casing is wood trim by others
- Steel, S56, & aluminum casing available with field installed clips
- Welded 3-1/2", 4" & 4-1/2" hinges
- Welded 2-3/4" & 4-7/8" strike prep
- Mylar 90 minute neutral and positive pressure fire label; wood or steel stud



REDIFRAME

1101 Technology Drive
800.633.7553
www.dunbarton.com

| Dothan, Alabama 36303
| 334.794.9184 fax
| sales@dunbarton.com



**Scan to go directly
to RediFrame
product webpage!**