

LEED®

SLIMFOLD BIFOLDS TECHNICAL LETTER

Slimfold bifold door models contain between 21.96% and 35.04% total applicable recycled content¹ depending on model type and door size. Multiply the cost of the door by the percentage for your model number to determine the final recycled content value applicable to Materials and Resources Credit 4: Recycled Content (LEED-NC). See table below for recycled content percentage by model number and door size.

Additionally, Dunbarton uses low VOC paints on the door frames, packages their products in recycled boxes, and the door frames are recyclable when it comes time for replacement.

Slimfold Bifold - 3'0 x 6'8 Doors

Model	Total Assembly % Pre-Consumer	Total Assembly % Post-Consumer	Total Applicable % (Post + 1/2 Pre)
4068 Bifold Glass	3.91%	26.28%	28.23%
5068 Bifold Glass	3.43%	23.00%	24.71%
6068 Bifold Glass	3.05%	20.44%	21.96%

Slimfold Bifold - 4'0 x 6'8 Doors

Model	Total Assembly % Pre-Consumer	Total Assembly % Post-Consumer	Total Applicable % (Post + 1/2 Pre)
4068 Bifold Glass	4.44%	29.79%	32.01%
5068 Bifold Glass	3.94%	26.43%	28.40%
6068 Bifold Glass	3.54%	23.75%	25.52%

Slimfold Bifold - 5'0 x 6'8 Doors

Model	Total Assembly % Pre-Consumer	Total Assembly % Post-Consumer	Total Applicable % (Post + 1/2 Pre)
4068 Bifold Glass	4.86%	32.61%	35.04%
5068 Bifold Glass	4.36%	29.26%	31.44%
6068 Bifold Glass	3.95%	26.53%	28.50%

Because doors are considered an assembly product these total have been calculated according to LEED standards by determining the weight of each component and its percentage of recycled content compared to the total weight of the assembly.

¹ Total recycled content is calculated as post-consumer recycled content + ½ pre-consumer recycled content.



1101 Technology Drive | Dothan, Alabama 36303
800.633.7553 | 334.794.9184 (fax)
www.dunbarton.com | sales@dunbarton.com